



BLOCK ENCLOSURE DETAIL "A"

CONSTRUCTION STANDARDS:

1. WALLS ARE TO BE OF DECORATIVE BLOCKS, MASONRY, OR SIMILAR MATERIALS. (NOT PRECISION BLOCK)
2. GATES ARE TO BE OF SOLID CONSTRUCTION (CHAIN LINK NOT PERMITTED).
3. PEDESTRIAN ACCESS IS REQUIRED IF IN RESIDENTIAL OR MULTI-TENANT AREAS. CONSULT WITH THE PLANNING DEPARTMENT FOR THOSE REQUIREMENTS.
4. DOUBLE SWING GATES SHALL HAVE THE SWIVEL SPOTS OUTSIDE OF THE OPENING AREA OF THE ENCLOSURE. SWIVEL POINTS SHALL BE ATTACHED TO CONCRETE FILLED STEEL POSTS/COLUMNS AT END OF WALLS
5. ENCLOSURE SHALL BE ON A LEVEL PAD AT GROUND LEVEL. THE AREA BETWEEN THE PAD AND THE PICK UP AREA SHALL BE PAVED 6" DEEP FOR THE WIDTH OF THE ENCLOSURE AND SHALL NOT EXCEED A GRADE OF 2%.

SIZE REQUIREMENTS

6. MINIMUM INSIDE DIMENSIONS SHALL BE AS SHOWN ON STANDARD PLAN 705 FOR COMMERCIAL, INDUSTRIAL, AND MULTI-TENANT FACILITIES.
7. COMMERCIAL ENCLOSURES SHALL BE CONFIGURED TO ALLOW THE ENCLOSURE OF TWO-THREE YARD DUMPSTERS.
8. INDUSTRIAL ENCLOSURES SHALL BE CONFIGURED TO ALLOW THE ENCLOSURE OF THREE-THREE YARD DUMPSTERS.
9. EACH BAY SHALL HAVE A SEPARATE PAIR OF GATES/DOORS THAT COMPLY WITH ITEM #2 ABOVE.
10. MINIMUM WALL OF GATE HEIGHT TO BE 6 FEET.



APPROVED BY:

 11/23/09
 CITY ENGINEER DATE
 KIP D. FIELD

CITY OF CORONA

**TRASH ENCLOSURE
 DETAILS**

REVISION	DESCRIPTION	BY	DATE

STANDARD PLAN NUMBER: **706**